



RECOMMENDED FOR MAINTENANCE

## SPECIFICATIONS & OPTIONS

OPENING SIZE	W=	H=
MFG. DOOR SIZE	W=	H=
PRIMARY VOLTAGE	208-240	440-480 575-600
DRIVE SIDE - (RH / LH)	OPERATOR SPEED (1/2 )	
CONTROL PANEL (ACS 50 / PLC)	SPRINGS	NO
	FULL ROLL COVERS	NO
WINDBARS		NO
WINDOWS (QTY.)	DETERMINED BY MFG. DOOR WIDTH	
FABRIC (BLACK SBR / GRAY EPDM / BLUE EPDM)		
DOOR ACTUATORS (QUANTITY)	PUSHBUTTON	<901>
	PULL SWITCH	<911>
	FLOOR LOOP	<930>
	PHOTOCELLS THRU BEAM	<940>
	REFLECTIVE	<941>
	MOTION DETECTOR	<950>
	RADIO RECEIVER	<925>

COMMENTS:

TABLE "A"

HEADER SIZE	MAX. DOOR SIZE	DIM. A	DIM. B
22"	DW<=18'-0" & DH<= 12'-0"	22.00" [559]	23.00" [584]
27"	DW<=18'-0" & DH<= 18'-0"	27.00" [686]	24.75" [629]

CUSTOMER:		APPROVED BY:		
LOCATION:		APPROVED WITH CHANGES BY:		
SALESMAN / DEALER:		DATE:	SCALE = N.T.S.	
		DESCRIPTION:		
				ULTRA TOUGH APPROVAL
DRAWING NO:		DESIGNER:	DATE:	
ULTRA TOUGH-005		J. REITZ	12/07/2007	