



RUBBER SHEETING

Universal reinforced and non-reinforced black neoprene rubber sheeting for applications such as header baffles and airport hangar doors. Partial rolls available.



1/16" X 50' THICKNESS NON-REINFORCED

ROLL WIDTH	PART NO.	0-99'	100'-299'	300'-899'	900'-1999'
6"	R116N-06-W	Call	Call	Call	Call
9"	R116N-09-W	Call	Call	Call	Call
12"	R116N-12-W	Call	Call	Call	Call
18"	R116N-18-W	Call	Call	Call	Call

1/8" X 50' THICKNESS NON-REINFORCED

ROLL WIDTH	PART NO.	0-99'	100'-299'	300'-899'	900'-1999'
6"	R018N-06-W	Call	Call	Call	Call
9"	R018N-09-W	Call	Call	Call	Call
12"	R018N-12-W	Call	Call	Call	Call
18"	R018N-18-W	Call	Call	Call	Call

1/8" X 50' THICKNESS SINGLE REINFORCED

ROLL WIDTH	PART NO.	0-99'	100'-299'	300'-899'	900'-1999'
6"	R018R-06-W	Call	Call	Call	Call
9"	R018R-09-W	Call	Call	Call	Call
12"	R018R-12-W	Call	Call	Call	Call
18"	R018R-18-W	Call	Call	Call	Call

3/16" X 33' THICKNESS TRIPLE REINFORCED

ROLL WIDTH	PART NO.	0-99'	100'-299'	300'-899'	900'-1999'
6"	R316R-06-W	Call	Call	Call	Call
9"	R316R-09-W	Call	Call	Call	Call
12"	R316R-12-W	Call	Call	Call	Call
18"	R316R-18-W	Call	Call	Call	Call

ROLLING STEEL DOOR BOTTOM SEAL

Made of a durable, black EPDM synthetic rubber. This long-lasting seal bolts between the bottom bars on rolling steel doors, and is an efficient one-piece installation. This seal is designed for applications where extreme temperatures changes (-50°-350°F) may occur. Also accepts pneumatic reversing hoses.

STOCK LENGTHS: 100' ROLLS

PART NO.	0-299'	300'-899'	900'-1999'	2000'+
BDS13-00-W	Call	Call	Call	Call

